

**0627s**

BLACK	0V	_____	) :       ( _____	425V ORANGE	
			) :       ( _____		0.25A
			) :       ( _____	0V GREY	
			) :       ( _____	425V ORANGE	
BLUE	230V-	_____ *	) :       ( _____	2.5V VIOLET	
			) :       ( -----ct _____	0V WHITE	3A
			) :       ( _____	2.5V VIOLET	
			) :       ( _____		
			) :       ( _____	3.15V YELLOW	
			) :       ( -----ct _____	0V GREEN	3A
			) :       ( _____	3.15V YELLOW	
			) :       ( _____		
BROWN	240V	_____	) :       ( _____	0V PINK (1)	
			) :       ( _____	7.5V PINK (1)	3A
			) :       ( _____		
			) :       ( _____	0V PINK (2)	
			) :       ( _____	7.5V PINK (2)	
YELLOW/GREEN		_____		ELECTROSTATIC SCREEN	

\* FOR PRIMARY WINDING WITH SOLID CORE WIRE AND SLEEVING

The solid wire inside the sleeving is coated with polyurethane and needs to be stripped away and tinned if the leads are shortened.

FOR FLEXIBLE LEADS PRIMARY -  
just cut short and isolate (INDIVIDUALLY) any spare connections

Note: A certain amount of mechanical hum is prevalent in mains transformers and can be amplified when bolting to your metal work. Therefore you may find a small rubber gasket or similar material is worth fitting to quieten this hum to its' minimum, but please ensure the frame is grounded to the supply safety earth.