

0912t

BLUE	0V	_____)	(_____	460V GREEN/RED	
)	(_____	410V WHITE/RED	0.14A
)	(_____		
)	(_____	0V GREEN	
)	(_____	410V WHITE/RED	
)	(_____		
BROWN	230V	_____)	(_____	460V GREEN/RED	
BLACK	0V	_____)	(_____	0V YELLOW	
)	(_____		1.5A
)	(-----ct	GREEN	
RED	10V	_____)	(_____	6.3V YELLOW	
)	(_____	0V BROWN	
)	(_____	5V BROWN	6A
)	(_____	0V ORANGE	
)	(_____	9V ORANGE	3A
)	(_____	0V GREY	
)	(_____	10V GREY	0.3A

*** FOR PRIMARY WINDING WITH SOLID CORE WIRE AND SLEEVING**

The solid wire inside the sleeving is coated with polyurethane and needs to be stripped away and tinned if the leads are shortened.

For secondary windings with solid core leads please follow the same process.

FOR FLEXIBLE LEADS PRIMARY AND SECONDARY

Just cut short and isolate any spare connections

NOTE: A certain amount of mechanical hum is prevalent in mains transformers and can be amplified when bolting to your metal work. Therefore you may find a small rubber gasket or similar material is worth fitting to quieten this hum to its' minimum, but please ensure the frame is grounded to the supply safety earth.