

1296i

RED_____)	(_____	common	GREY	
)	(_____	-55dB	BLUE-----	
)	(_____	-46dB	PINK	
)	(_____	-40dB	VIOLET	
)	(_____	-36dB	BROWN	red sleeve
)	(_____	-34db	GREEN	
)	(_____	-32dB	WHITE	
)	(_____	-30db	YELLOW	
)	(_____			
)	(_____	-28dB	BLUE-----	
)	(_____	-26dB	PINK	
)	(_____	-24dB	VIOLET	
)	(_____	-22dB	BROWN	orange sleeve
)	(_____	-20dB	GREEN	
)	(_____	-18dB	WHITE	
)	(_____	-16dB	YELLOW	
)	(_____			
)	(_____	-14dB	BLUE-----	
)	(_____	-12dB	PINK	
)	(_____	-10dB	VIOLET	
)	(_____	- 8dB	BROWN	green sleeve
)	(_____	- 6dB	GREEN	
)	(_____	- 4dB	WHITE	
)	(_____	- 2dB	YELLOW---	
ORANGE_____)	(_____	0dB	BLACK	

ORANGE IS THE HOT SIDE OF THE PRIMARY

BLACK (OR ANY TAP) IS HOT FOR SECONDARY

GREY WOULD NORMALLY BE THE COLD OF THE SECONDARY

TYPE 1296i Custom tapped attenuator