9532

| | 1.1 | 1 | |
|-------|-------|---|--------------|
| +HT |) | (1 | – RED |
| |) | (| _ BLUE |
| |) [[| İ | _ |
| |) [[| (2 | RED |
| |) | (| _ BLUE |
| 43% |) | l İ | |
| |) [[| (3 | RED |
| |) [| (| BLUE |
| |) [| | |
| |) [[| (4 | RED |
| ANODE |) [| İ | _ BLUE |
| | į į | İİ | |
| | 43% | 43%) 43%) 0 1 1 1 1 1 1 1 1 1 | 43%) (|

OUTPUT WINDINGS.

There are FOUR EQUAL SECONDARY WINDINGS which can be arranged for loads of 1, 4, 8/9 or 15/16 ohms thus:-

| 1 ohm | 4 ohm | 8/9 ohm | 15/16 ohm |
|----------|----------|---------|-----------|
| RED | RED | RED | RED |
| | <u> </u> | İ | <u></u> |
| (1(2(3(4 | (1(2 | (1(2 | (1 |
| (_(_(_(| (_(| [(_(| (|
| BLUE | (3(4 | (3 | (2 |
| | (_(| (| (|
| | BLUE | (4 | (3 |
| | | (| (|
| | | BLUE | (4 |
| | | | (|
| | | | BLUE |