


9580 1:12.5 High Z Cartridge Transfomer

Very high performance transformer for use with cartridges with an impedance in the range 25 to 100 ohms. Bandwidth 5 Hz to 60 kHz. Suitable for Denon DL - 304 and DL - 103. Two transformers are required for stereo.



9580f

primary	ORANGE) () (- GREEN	secondary
	RED) (BLUE	
	BLACK = ELECTROSTATIC SCREEN			

 ${\bf DO}~{\bf NOT}$ screw into transformer more than 3 mm

Data sheet can be found on our website www.sowter.co.uk, click on cartridge button and then click on 9580 link

9580 1:12.5 High Z Cartridge Transfomer

Very high performance transformer for use with cartridges with an impedance in the range 25 to 100 ohms. Bandwidth 5 Hz to 60 kHz. Suitable for Denon DL - 304 and DL - 103. Two transformers are required for stereo.

<u>9580g</u>

Data sheet can be found on our website $\underline{\text{www.sowter.co.uk,}}$ click on cartridge button and then click on 9580 link

9580 1:12.5 High Z Cartridge Transfomer

Very high performance transformer for use with cartridges with an impedance in the range 25 to 100 ohms. Bandwidth 5 Hz to 60 kHz. Suitable for Denon DL - 304 and DL - 103. Two transformers are required for stereo.